

BRAWO SYSTEMS
PICO • LIGHT CURING SYSTEM



BRAWO® Pico
smart • efficient • small



LIGHT CURING THE SMART WAY

SAVE TIME AND EFFORT

The innovative and unique LED head allows simultaneous retraction and inversion of the liner by means of unlocking. Curing is thus carried out immediately after installation of the liner – without the need for additional insertion of the eel.

BRAWO® Pico stands for maximum flexibility and is perfectly matched to the installation of the BRAWOLINER® product line.



LED head



Accessories



Control box

BRAWO® PICO – SMALL BUT MIGHTY

BRAWO® Pico is the first system specifically designed for use in very small waste water pipes. These are usually found inside buildings (in-house). The innovative light curing for small nominal diameters is unique. The high installation safety and the usual high quality of BRAWO® Tech, the brand for high-quality rehabilitation equipment, is guaranteed.

Technical data for BRAWO® Pico

Field of application:	possible from DN 50 to DN 100
Range:	25 m (hose length)
Retraction speed:	from 0.1 to 2.0 m/min
Head diameter:	24 mm
Weight:	approx. 25 kg
Dimensions (L x W x H mm):	440 x 425 x 595

smart

- Intelligent LED head
- Installation log and interface to mobile terminal device (USB, W-LAN)
- Changeable hose package with LED head
- Integrated operating hours control and temperature monitoring

efficient

- Low power consumption with high light output
- 20 high-power UV LEDs with extremely high efficiency
- Saves a complete operation, only one access point necessary

small

- Very fast curing
- Very good bend flexibility, 87° possible from DN 50 upwards
- Easy transport thanks to compact, lightweight modular design
- Extremely small construction, particularly suitable for in-house rehabilitation